

WHAT IS CLAIMED IS:

1. A waterproof grommet comprising:

an elastic grommet main body passing an electric wire therethrough; and

5 a hold member being disposed on an outer surface of said grommet main body at an intermediate portion in a lengthwise direction of said grommet main body, whereby said hold member is mountable on a mounting part.

2. The waterproof grommet according to claim 1, wherein said
10 grommet main body has a cylindrical portion and bellows portions at the both side thereof, wherein said hold member is disposed on said cylindrical portion.

3. The waterproof grommet according to claim 1 or 2, wherein said hold member comprises a ring portion and a hold portion
15 provided at said ring portion, said ring portion capable of being opened and closed and capable of being locked.

4. The waterproof grommet according to claim 3, wherein said hold portion comprises a pair of hook portions for holding a hinge link.

20 5. The waterproof grommet according to any one of claim 4, wherein said hold member is a rigid member.

6. The waterproof grommet according to any one of claim 5, wherein said cylindrical portion is continued to said bellows portion through a peripheral flange.

25 7. The waterproof grommet according to any one of claim 3, wherein said cylindrical portion is provided with a projecting

portion, and said ring portion is provided with an engaging portion corresponding to said projecting portion.

8. The waterproof grommet according to claim 7, wherein a pair of said projecting portions is oppositely disposed, and
5 right-and-left side marks are provided respectively on said pair of projecting portions or in a vicinity of said pair of projecting portions, and a direction mark for pointing one of said right-and-left side marks is provided on said ring portion.
9. The waterproof grommet according to claim 8, wherein a
10 plurality of projections for preventing crushing and checking position is disposed together with said projecting portions on a same straight line at said bellows portion.